



74AVC4T245Q

4-Bit Dual-Supply

Translating Transceiver with Configurable

Voltage Translation and 3-State Outputs

GENERAL DESCRIPTION

The 74AVC4T245Q is a 4-bit, dual-supply voltage level transceiver with 3-state outputs and bidirectional level translation. The device can be used as two 2-bit transceivers or one 4-bit transceiver. The nAn and nBn are four data input-output ports. nDIR are the direction control inputs and n $\overline{\text{OE}}$ are the output enable inputs. V_{CCA} and V_{CCB} are the supply pins. The supply voltage of V_{CCA} and V_{CCB} can range from 0.8V to 3.6V, making the device suitable for bidirectional translating among any of the 0.8V, 1.2V, 1.5V, 1.8V, 2.5V and 3.3V voltage nodes. The nAn, nDIR and n $\overline{\text{OE}}$ signals are referenced to V_{CCA} and nBn signals are referenced to V_{CCB}.

When nDIR is set high, it allows transmission from nAn to nBn. When nDIR is set low, it allows transmission from nBn to nAn. n $\overline{\text{OE}}$ can be used to make the outputs disabled so that the buses are effectively isolated. In suspend mode, both nAn and nBn are in high-impedance state when either V_{CCA} or V_{CCB} input is at GND level.

This device is highly suitable for partial power-down applications using power-off leakage current (I_{OFF}) circuit. When the device is powered down, the current backflow will be prevented from passing through the device.

This device is AEC-Q100 qualified (Automotive Electronics Council Standard Q100 Grade 1) and the use of this device is suitable for automotive applications.

FEATURES

- **AEC-Q100 Qualified for Automotive Applications**
Device Temperature Grade 1
T_A = -40°C to +125°C
- **V_{CCA} Supply Voltage Range: 0.8V to 3.6V**
- **V_{CCB} Supply Voltage Range: 0.8V to 3.6V**
- **Inputs Accept Voltages up to 3.6V**
- **+12mA/-12mA Output Current**
- **Data Rates:**
 - ◆ **380Mbps (≥ 1.8V to 3.3V Translation)**
 - ◆ **200Mbps (≥ 1.1V to 3.3V Translation)**
 - ◆ **200Mbps (≥ 1.1V to 2.5V Translation)**
 - ◆ **200Mbps (≥ 1.1V to 1.8V Translation)**
 - ◆ **150Mbps (≥ 1.1V to 1.5V Translation)**
 - ◆ **100Mbps (≥ 1.1V to 1.2V Translation)**
- **Outputs in High-Impedance State when V_{CCA} or V_{CCB} = 0V**
- **-40°C to +125°C Operating Temperature Range**
- **Available in a Green TSSOP-16 Package**

APPLICATIONS

Personal Electronic
Industrial Equipment
Enterprise Infrastructures
Telecom Equipment

4-Bit Dual-Supply Translating Transceiver with 74AVC4T245Q Configurable Voltage Translation and 3-State Outputs


PACKAGE/ORDERING INFORMATION

MODEL	PACKAGE DESCRIPTION	SPECIFIED TEMPERATURE RANGE	ORDERING NUMBER	PACKAGE TOP MARKING	PACKING OPTION
74AVC4T245Q	TSSOP-16	-40°C to +125°C	74AVC4T245QTS16G/TR	MEATS16 XXXXX	Tape and Reel, 4000

MARKING INFORMATION

NOTE: XXXXX = Date Code, Trace Code and Vendor Code.

XXXXX



Green (RoHS & HSF): SG Micro Corp defines "Green" to mean Pb-Free (RoHS compatible) and free of halogen substances. If you have additional comments or questions, please contact your SGMICRO representative directly.

ABSOLUTE MAXIMUM RATINGS ⁽¹⁾

Supply Voltage Range, V_{CCA}	-0.5V to 4.6V
Supply Voltage Range, V_{CCB}	-0.5V to 4.6V
Input Voltage Range, V_I ⁽²⁾	-0.5V to 4.6V
Output Voltage Range, V_O ⁽²⁾	
Suspend or 3-State Mode	-0.5V to 4.6V
Active Mode	
A Ports	-0.5V to MIN (4.6V, $V_{CCA} + 0.5V$)
B Ports	-0.5V to MIN (4.6V, $V_{CCB} + 0.5V$)
Output Current, I_O ($V_O = 0V$ to V_{CC})	
High-State or Low-State	$\pm 50mA$
Supply Current, I_{CC} , per V_{CCA} or V_{CCB} Pin	100mA
Ground Current, I_{GND} , per GND Pin	-100mA
Input Clamp Current, I_{IK} ($V_I < 0$).....	-50mA
Output Clamp Current, I_{OK} ($V_O < 0$).....	-50mA
Junction Temperature ⁽³⁾	+150°C
Storage Temperature Range	-65°C to +150°C
Lead Temperature (Soldering, 10s).....	+260°C
ESD Susceptibility	
HBM.....	6000V
CDM	1000V

RECOMMENDED OPERATING CONDITIONS

Supply Voltage Range, V_{CCA}	0.8V to 3.6V
Supply Voltage Range, V_{CCB}	0.8V to 3.6V
Input Voltage Range, V_I	0V to 3.6V
Output Voltage Range, V_O	
Suspend or 3-State Mode	0V to 3.6V
Active Mode	
A Ports	0V to V_{CCA}
B Ports	0V to V_{CCB}
High-State or Low-State Output Current, I_O	$\pm 12mA$
Input Transition Rise or Fall Rate, $\Delta t/\Delta V$	
$V_{CCI} = 0.8V$ to 3.6V.....	5ns/V (MAX)
Operating Temperature Range	-40°C to +125°C

OVERSTRESS CAUTION

1. Stresses beyond those listed in Absolute Maximum Ratings may cause permanent damage to the device. Exposure to absolute maximum rating conditions for extended periods may affect reliability. Functional operation of the device at any conditions beyond those indicated in the Recommended Operating Conditions section is not implied.
2. The input and output voltage ratings may be exceeded if the input and output clamp current ratings are observed.
3. The performance capability of a high-performance integrated circuit in conjunction with its thermal environment can create junction temperatures which are detrimental to reliability.

ESD SENSITIVITY CAUTION

This integrated circuit can be damaged if ESD protections are not considered carefully. SGMICRO recommends that all integrated circuits be handled with appropriate precautions. Failure to observe proper handling and installation procedures can cause damage. ESD damage can range from subtle performance degradation to complete device failure. Precision integrated circuits may be more susceptible to damage because even small parametric changes could cause the device not to meet the published specifications.


DISCLAIMER

SG Micro Corp reserves the right to make any change in circuit design, or specifications without prior notice.

4-Bit Dual-Supply Translating Transceiver with Configurable Voltage Translation and 3-State Outputs

74AVC4T245Q

LOGIC DIAGRAM



FUNCTION TABLE

SUPPLY VOLTAGE	CONTROL INPUT		INPUT/OUTPUT	
	$V_{CCA}, V_{CCB}^{(1)}$	\overline{nOE}	$nDIR$	nAn
0.8V to 3.6V	L	L	$nAn = nBn$	Inputs
0.8V to 3.6V	L	H	Inputs	$nBn = nAn$
0.8V to 3.6V	H	X	Z	Z
GND ⁽²⁾	X	X	Z	Z


H = High Voltage Level
 L = Low Voltage Level
 Z = High-Impedance State
 X = Don't Care

NOTES:

- The nAn , $nDIR$ and \overline{nOE} signals are referenced to V_{CCA} . The nBn signals are referenced to V_{CCB} .
- If at least one of V_{CCA} or V_{CCB} is at GND level, the device enters suspend mode.

74AVC4T245Q 4-Bit Dual-Supply Translating Transceiver with Configurable Voltage Translation and 3-State Outputs

PIN CONFIGURATION



PIN DESCRIPTION

PIN	NAME	FUNCTION
1	V_{CCA}	Supply Voltage V_{CCA} . The nA_n , $nDIR$ and nOE signals are referenced to V_{CCA} .
2, 3	1DIR, 2DIR	Direction Control Inputs.
4, 5	1A1, 1A2	Data Inputs/Outputs.
6, 7	2A1, 2A2	Data Inputs/Outputs.
8, 9	GND	Ground.
11, 10	2B1, 2B2	Data Inputs/Outputs.
13, 12	1B1, 1B2	Data Inputs/Outputs.
15, 14	$1OE$, $2OE$	Output Enable Inputs (Active Low).
16	V_{CCB}	Supply Voltage V_{CCB} . The nB_n signals are referenced to V_{CCB} .

4-Bit Dual-Supply Translating Transceiver with 74AVC4T245Q Configurable Voltage Translation and 3-State Outputs

ELECTRICAL CHARACTERISTICS

(Full = -40°C to +125°C, all typical values are at T_A = +25°C. V_{CCI} is the supply voltage associated with the data input port, V_{CCO} is the supply voltage associated with the data output port, unless otherwise noted.)

PARAMETER	SYMBOL	CONDITIONS		TEMP	MIN	TYP	MAX	UNITS
High-Level Input Voltage	V _{IH}	Data Inputs	V _{CCI} = 0.8V	Full	0.70 × V _{CCI}			V
			V _{CCI} = 1.1V to 1.95V	Full	0.65 × V _{CCI}			
			V _{CCI} = 2.3V to 2.7V	Full	1.6			
			V _{CCI} = 3.0V to 3.6V	Full	2			
		nDIR, n $\overline{\text{OE}}$ inputs	V _{CCA} = 0.8V	Full	0.70 × V _{CCA}			V
			V _{CCA} = 1.1V to 1.95V	Full	0.65 × V _{CCA}			
			V _{CCA} = 2.3V to 2.7V	Full	1.6			
			V _{CCA} = 3.0V to 3.6V	Full	2			
Low-Level Input Voltage	V _{IL}	Data Inputs	V _{CCI} = 0.8V	Full			0.30 × V _{CCI}	V
			V _{CCI} = 1.1V to 1.95V	Full			0.35 × V _{CCI}	
			V _{CCI} = 2.3V to 2.7V	Full			0.7	
			V _{CCI} = 3.0V to 3.6V	Full			0.8	
		nDIR, n $\overline{\text{OE}}$ inputs	V _{CCA} = 0.8V	Full			0.30 × V _{CCA}	V
			V _{CCA} = 1.1V to 1.95V	Full			0.35 × V _{CCA}	
			V _{CCA} = 2.3V to 2.7V	Full			0.7	
			V _{CCA} = 3.0V to 3.6V	Full			0.8	
High-level Output Voltage	V _{OH}	V _I = V _{IH}	I _O = -100μA, V _{CCA} = V _{CCB} = 0.8V to 3.6V	Full	V _{CCO} - 0.1	V _{CCO} - 0.01		V
			I _O = -3mA, V _{CCA} = V _{CCB} = 1.1V	Full	0.85	0.98		
			I _O = -6mA, V _{CCA} = V _{CCB} = 1.4V	Full	1.05	1.22		
			I _O = -8mA, V _{CCA} = V _{CCB} = 1.65V	Full	1.20	1.43		
			I _O = -9mA, V _{CCA} = V _{CCB} = 2.3V	Full	1.75	2.09		
			I _O = -12mA, V _{CCA} = V _{CCB} = 3.0V	Full	2.30	2.75		
Low-Level Output Voltage	V _{OL}	V _I = V _{IL}	I _O = 100μA, V _{CCA} = V _{CCB} = 0.8V to 3.6V	Full		0.01	0.1	V
			I _O = 3mA, V _{CCA} = V _{CCB} = 1.1V	Full		0.10	0.25	
			I _O = 6mA, V _{CCA} = V _{CCB} = 1.4V	Full		0.16	0.35	
			I _O = 8mA, V _{CCA} = V _{CCB} = 1.65V	Full		0.19	0.45	
			I _O = 9mA, V _{CCA} = V _{CCB} = 2.3V	Full		0.18	0.55	
			I _O = 12mA, V _{CCA} = V _{CCB} = 3.0V	Full		0.23	0.70	

4-Bit Dual-Supply Translating Transceiver with 74AVC4T245Q Configurable Voltage Translation and 3-State Outputs

ELECTRICAL CHARACTERISTICS (continued)

(Full = -40°C to +125°C, all typical values are at T_A = +25°C. V_{CCI} is the supply voltage associated with the data input port, V_{CCO} is the supply voltage associated with the data output port, unless otherwise noted.)

PARAMETER	SYMBOL	CONDITIONS	TEMP	MIN	TYP	MAX	UNITS	
Input Leakage Current	I _I	nDIR, nOE inputs, V _I = 0V or 3.6V, V _{CCA} = V _{CCB} = 0.8V to 3.6V	Full		±0.01	±5	μA	
Off-State Output Current ⁽¹⁾	I _{OZ}	V _{CCA} = V _{CCB} = 3.6V, A or B ports, V _O = 0V or V _{CCO}	Full		±0.01	±5	μA	
		V _{CCA} = 3.6V, V _{CCB} = 0V, suspend mode A ports, V _O = 0V or V _{CCO}	Full		±0.01	±5		
		V _O = 0V or V _{CCO} , V _{CCA} = 0V, V _{CCB} = 3.6V	Full		±0.01	±5		
Power-Off Leakage Current	I _{OFF}	V _{CCA} = 0V, V _{CCB} = 0.8V to 3.6V, A ports, V _I or V _O = 0V to 3.6V	Full		±0.01	±5	μA	
		V _{CCB} = 0V, V _{CCA} = 0.8V to 3.6V, B ports, V _I or V _O = 0V to 3.6V	Full		±0.01	±5		
Supply Current	I _{CC}	A ports, V _I = 0V or V _{CCI} , I _O = 0A	V _{CCA} = 0.8V to 3.6V, V _{CCB} = 0.8V to 3.6V	Full		1.4	10	μA
			V _{CCA} = 1.1V to 3.6V, V _{CCB} = 1.1V to 3.6V	Full		1.2	10	
			V _{CCA} = 3.6V, V _{CCB} = 0V	Full		0.01	5	
			V _{CCA} = 0V, V _{CCB} = 3.6V	Full		0.01	5	
		B ports, V _I = 0V or V _{CCI} , I _O = 0A	V _{CCA} = 0.8V to 3.6V, V _{CCB} = 0.8V to 3.6V	Full		0.8	10	μA
			V _{CCA} = 1.1V to 3.6V, V _{CCB} = 1.1V to 3.6V	Full		0.7	10	
			V _{CCA} = 3.6V, V _{CCB} = 0V	Full		0.01	5	
			V _{CCA} = 0V, V _{CCB} = 3.6V	Full		0.01	5	
		A plus B ports (I _{CCA} + I _{CCB}), I _O = 0A, V _I = 0V or V _{CCI} , V _{CCA} = 0.8V to 3.6V, V _{CCB} = 0.8V to 3.6V		Full		1.4	15	μA
		A plus B ports (I _{CCA} + I _{CCB}), I _O = 0A, V _I = 0V or V _{CCI} , V _{CCA} = 1.1V to 3.6V, V _{CCB} = 1.1V to 3.6V		Full		1.2	15	μA
Input Capacitance	C _I	nDIR, nOE inputs, V _I = 0V or 3.3V, V _{CCA} = V _{CCB} = 3.3V	+25°C		3.2		pF	
Input/Output Capacitance	C _{I/O}	A and B ports, suspend mode, V _O = V _{CCO} or GND, V _{CCA} = V _{CCB} = 3.3V	+25°C		4.5		pF	

NOTE:

- For I/O ports, the parameter I_{OZ} includes the input leakage current.

4-Bit Dual-Supply Translating Transceiver with 74AVC4T245Q Configurable Voltage Translation and 3-State Outputs

ELECTRICAL CHARACTERISTICS (continued)

Typical Total Supply Current ($I_{CCA} + I_{CCB}$)

($T_A = +25^\circ\text{C}$, unless otherwise noted.)

V_{CCA}	V_{CCB}							UNITS
	0V	0.8V	1.2V	1.5V	1.8V	2.5V	3.3V	
0V	0	0.01	0.01	0.01	0.01	0.01	0.01	μA
0.8V	0.01	0.01	0.01	0.01	0.03	0.20	0.60	μA
1.2V	0.01	0.01	0.01	0.01	0.01	0.10	0.40	μA
1.5V	0.01	0.01	0.01	0.01	0.01	0.03	0.30	μA
1.8V	0.01	0.05	0.01	0.01	0.01	0.01	0.20	μA
2.5V	0.01	0.40	0.20	0.06	0.02	0.01	0.02	μA
3.3V	0.01	1.10	0.70	0.50	0.30	0.03	0.01	μA

Typical Power Dissipation Capacitance

($T_A = +25^\circ\text{C}$, $V_{CCA} = V_{CCB}$, unless otherwise noted.)

PARAMETER	SYMBOL	CONDITIONS	$V_{CCA} = V_{CCB}$						UNITS
			0.8V	1.2V	1.5V	1.8V	2.5V	3.3V	
Power Dissipation Capacitance ⁽¹⁾⁽²⁾	C_{PD}	A ports: (direction nAn to nBn), output enabled	2.0	2.0	2.1	2.2	2.4	2.7	pF
		A ports: (direction nAn to nBn), output disabled	0.6	0.7	0.7	0.7	0.8	0.9	
		A ports: (direction nBn to nAn), output enabled	16.0	16.1	16.2	16.3	16.5	16.7	
		A ports: (direction nBn to nAn), output disabled	1.4	1.3	1.4	1.4	1.6	1.7	
		B ports: (direction nAn to nBn), output enabled	16.0	16.1	16.2	16.3	16.5	16.7	
		B ports: (direction nAn to nBn), output disabled	1.4	1.3	1.4	1.4	1.6	1.7	
		B ports: (direction nBn to nAn), output enabled	2.0	2.0	2.1	2.2	2.4	2.7	
		B ports: (direction nBn to nAn), output disabled	0.6	0.7	0.7	0.7	0.8	0.9	

NOTES:

1. C_{PD} is used to determine the dynamic power dissipation (P_D in μW).

$$P_D = C_{PD} \times V_{CC}^2 \times f_i \times N + \Sigma(C_L \times V_{CC}^2 \times f_o)$$

where:

f_i = Input frequency in MHz.

f_o = Output frequency in MHz.

C_L = Output load capacitance in pF.

V_{CC} = Supply voltage in Volts.

N = Number of inputs switching.

$\Sigma(C_L \times V_{CC}^2 \times f_o)$ = Sum of the outputs.

2. $f_i = 10\text{MHz}$, $V_i = \text{GND to } V_{CC}$, $t_R = t_F = 1\text{ns}$, $C_L = 0\text{pF}$, $R_L = \infty$.

4-Bit Dual-Supply Translating Transceiver with 74AVC4T245Q Configurable Voltage Translation and 3-State Outputs

DYNAMIC CHARACTERISTICS

Typical Dynamic Characteristics at $V_{CCA} = 0.8V$ and $T_A = +25^\circ C$

(For test circuit, see Figure 1, for waveforms see Figure 2 and Figure 3, unless otherwise noted.)

PARAMETER	SYMBOL	CONDITIONS	V_{CCB}						UNITS
			0.8V	1.2V	1.5V	1.8V	2.5V	3.3V	
Propagation Delay ⁽¹⁾	t_{PD}	nAn to nBn	31.9	11.1	9.8	9.5	9.7	10.2	ns
		nBn to nAn	33.8	21.0	18.0	17.7	17.2	17.1	
Disable Time	t_{DIS}	\overline{nOE} to nAn	30.6	30.5	30.6	32.6	32.5	39.0	ns
		\overline{nOE} to nBn	31.2	20.2	19.3	19.4	18.8	19.8	
Enable Time	t_{EN}	\overline{nOE} to nAn	44.4	44.2	44.2	44.2	44.4	44.3	ns
		\overline{nOE} to nBn	38.4	18.2	16.9	16.6	16.8	17.8	

NOTE:

1. t_{PD} is the same as t_{PLH} and t_{PHL} , t_{DIS} is the same as t_{PLZ} and t_{PHZ} , t_{EN} is the same as t_{PZL} and t_{PZH} .

Typical Dynamic Characteristics at $V_{CCB} = 0.8V$ and $T_A = +25^\circ C$

(For test circuit, see Figure 1, for waveforms see Figure 2 and Figure 3, unless otherwise noted.)

PARAMETER	SYMBOL	CONDITIONS	V_{CCA}						UNITS
			0.8V	1.2V	1.5V	1.8V	2.5V	3.3V	
Propagation Delay ⁽¹⁾	t_{PD}	nAn to nBn	30.2	26.6	25.9	24.6	24.1	24.0	ns
		nBn to nAn	32.0	11.1	9.8	9.4	9.4	9.9	
Disable Time	t_{DIS}	\overline{nOE} to nAn	30.5	9.0	6.3	5.8	4.3	5.5	ns
		\overline{nOE} to nBn	31.1	21.5	20.1	21.1	20.6	26.7	
Enable Time	t_{EN}	\overline{nOE} to nAn	44.3	10.4	6.5	5.0	3.8	3.3	ns
		\overline{nOE} to nBn	38.9	30.5	29.0	28.1	27.8	27.5	

NOTE:

1. t_{PD} is the same as t_{PLH} and t_{PHL} , t_{DIS} is the same as t_{PLZ} and t_{PHZ} , t_{EN} is the same as t_{PZL} and t_{PZH} .

4-Bit Dual-Supply Translating Transceiver with 74AVC4T245Q Configurable Voltage Translation and 3-State Outputs

DYNAMIC CHARACTERISTICS (continued)

Dynamic Characteristics

(For test circuit, see Figure 1, for waveforms see Figure 2 and Figure 3. Full = -40°C to +125°C, all typical values are at T_A = +25°C, unless otherwise noted.)

PARAMETER	SYMBOL	CONDITIONS	V _{CCB}									UNITS
			1.2V ± 0.1V			1.5V ± 0.1V			1.8V ± 0.15V			
			MIN ⁽¹⁾	TYP	MAX ⁽¹⁾	MIN ⁽¹⁾	TYP	MAX ⁽¹⁾	MIN ⁽¹⁾	TYP	MAX ⁽¹⁾	
V_{CCA} = 1.1V to 1.3V												
Propagation Delay ⁽²⁾	t _{PD}	nAn to nBn	0.5	8.9	15.0	0.5	6.5	10.5	0.5	5.9	9.4	ns
		nBn to nAn	0.5	8.9	14.9	0.3	7.6	12.3	0.1	7.1	11.7	
Disable Time	t _{DIS}	n $\overline{O\!E}$ to nAn	1.8	10.5	15.0	1.8	10.2	15.4	1.8	10.5	15.8	ns
		n $\overline{O\!E}$ to nBn	1.9	10.0	15.2	1.9	8.4	12.3	1.9	8.0	11.7	
Enable Time	t _{EN}	n $\overline{O\!E}$ to nAn	1.4	12.6	20.3	1.4	12.9	20.3	1.4	13.2	20.4	ns
		n $\overline{O\!E}$ to nBn	1.1	11.1	17.5	1.1	8.9	13.2	1.1	8.3	12.0	
V_{CCA} = 1.4V to 1.6V												
Propagation Delay ⁽²⁾	t _{PD}	nAn to nBn	0.3	7.4	12.1	0.3	5.4	8.4	0.3	4.7	7.4	ns
		nBn to nAn	0.5	6.4	10.4	0.3	5.3	8.4	0.1	4.8	7.6	
Disable Time	t _{DIS}	n $\overline{O\!E}$ to nAn	1.8	6.9	11.8	1.8	6.3	11.8	1.5	7.4	11.8	ns
		n $\overline{O\!E}$ to nBn	1.9	7.7	13.0	1.9	6.0	11.9	1.9	5.6	10.6	
Enable Time	t _{EN}	n $\overline{O\!E}$ to nAn	1.1	7.1	10.9	1.1	7.3	11.0	0.7	7.5	11.0	ns
		n $\overline{O\!E}$ to nBn	1.4	8.9	11.1	1.1	6.6	9.0	0.9	5.7	9.0	
V_{CCA} = 1.65V to 1.95V												
Propagation Delay ⁽²⁾	t _{PD}	nAn to nBn	0.1	7.0	11.7	0.1	4.8	7.7	0.1	4.1	6.6	ns
		nBn to nAn	0.5	5.8	9.3	0.3	4.7	7.0	0.1	4.1	6.5	
Disable Time	t _{DIS}	n $\overline{O\!E}$ to nAn	1.8	6.0	11.8	1.6	5.2	10.0	1.8	5.5	10.0	ns
		n $\overline{O\!E}$ to nBn	1.7	7.2	12.5	1.7	5.3	11.4	1.6	5.1	10.1	
Enable Time	t _{EN}	n $\overline{O\!E}$ to nAn	1.0	5.4	8.5	1.0	5.5	8.5	1.0	5.4	8.5	ns
		n $\overline{O\!E}$ to nBn	1.2	8.1	13.4	1.2	5.6	10.7	1.0	5.1	8.7	
V_{CCA} = 2.3V to 2.7V												
Propagation Delay ⁽²⁾	t _{PD}	nAn to nBn	0.1	6.6	11.1	0.1	4.4	7.1	0.1	3.7	5.9	ns
		nBn to nAn	0.5	5.2	8.4	0.3	4.1	6.2	0.1	3.5	5.5	
Disable Time	t _{DIS}	n $\overline{O\!E}$ to nAn	4.3	5.0	7.4	1.0	4.1	7.4	1.0	4.9	7.4	ns
		n $\overline{O\!E}$ to nBn	6.7	6.7	12.0	1.5	4.8	10.9	1.3	4.5	9.6	
Enable Time	t _{EN}	n $\overline{O\!E}$ to nAn	0.7	3.7	5.8	0.7	3.8	5.8	0.7	3.8	5.8	ns
		n $\overline{O\!E}$ to nBn	0.9	7.3	12.9	0.9	4.9	10.2	0.8	4.3	8.2	
V_{CCA} = 3.0V to 3.6V												
Propagation Delay ⁽²⁾	t _{PD}	nAn to nBn	0.1	6.4	10.8	0.1	4.3	6.8	0.1	3.6	5.7	ns
		nBn to nAn	0.5	5.2	8.3	0.3	3.9	5.8	0.3	3.3	5.0	
Disable Time	t _{DIS}	n $\overline{O\!E}$ to nAn	0.7	3.8	6.7	0.7	3.7	6.7	0.7	3.9	6.7	ns
		n $\overline{O\!E}$ to nBn	1.4	6.6	11.8	1.4	4.7	10.8	1.2	4.3	9.5	
Enable Time	t _{EN}	n $\overline{O\!E}$ to nAn	0.6	3.2	4.7	0.6	3.1	4.7	0.6	3.2	4.7	ns
		n $\overline{O\!E}$ to nBn	0.8	7.2	12.9	0.8	4.6	10.1	0.6	4.0	8.0	

NOTES:

- Specified by design and characterization, not production tested.
- t_{PD} is the same as t_{PLH} and t_{PHL}, t_{DIS} is the same as t_{PLZ} and t_{PHZ}, t_{EN} is the same as t_{PZL} and t_{PZH}.

4-Bit Dual-Supply Transceiver with 74AVC4T245Q Configurable Voltage Translation and 3-State Outputs

DYNAMIC CHARACTERISTICS (continued)

Dynamic Characteristics

(For test circuit, see Figure 1, for waveforms see Figure 2 and Figure 3. Full = -40°C to +125°C, all typical values are at T_A = +25°C, unless otherwise noted.)


PARAMETER	SYMBOL	CONDITIONS	V _{CCB}						UNITS
			2.5V ± 0.2V			3.3V ± 0.3V			
			MIN ⁽¹⁾	TYP	MAX ⁽¹⁾	MIN ⁽¹⁾	TYP	MAX ⁽¹⁾	
V_{CCA} = 1.1V to 1.3V									
Propagation Delay ⁽²⁾	t _{PD}	nAn to nBn	0.5	5.3	8.5	0.5	5.1	8.4	ns
		nBn to nAn	0.1	6.6	11.1	0.1	6.4	10.7	
Disable Time	t _{DIS}	n \overline{OE} to nAn	1.8	10.2	15.5	1.8	11.2	16.0	ns
		n \overline{OE} to nBn	1.4	7.4	10.8	1.2	8.7	12.4	
Enable Time	t _{EN}	n \overline{OE} to nAn	1.4	14.5	22.5	1.4	15.9	23.4	ns
		n \overline{OE} to nBn	1.0	7.7	11.2	1.0	7.6	11.1	
V_{CCA} = 1.4V to 1.6V									
Propagation Delay ⁽²⁾	t _{PD}	nAn to nBn	0.3	4.1	6.2	0.3	3.9	5.8	ns
		nBn to nAn	0.1	4.3	6.9	0.1	4.2	6.7	
Disable Time	t _{DIS}	n \overline{OE} to nAn	1.3	6.3	11.8	1.6	8.3	11.8	ns
		n \overline{OE} to nBn	1.4	5.0	8.7	1.2	5.3	8.9	
Enable Time	t _{EN}	n \overline{OE} to nAn	0.7	7.7	11.1	0.4	8.1	11.9	ns
		n \overline{OE} to nBn	0.9	5.4	7.9	0.9	5.2	7.7	
V_{CCA} = 1.65V to 1.95V									
Propagation Delay ⁽²⁾	t _{PD}	nAn to nBn	0.1	3.5	5.4	0.3	3.3	5.1	ns
		nBn to nAn	0.1	3.7	5.9	0.1	3.6	5.7	
Disable Time	t _{DIS}	n \overline{OE} to nAn	1.3	5.1	10.0	1.6	6.5	10.0	ns
		n \overline{OE} to nBn	1.2	4.4	8.1	1.0	4.7	8.1	
Enable Time	t _{EN}	n \overline{OE} to nAn	0.6	5.5	8.5	0.4	5.9	8.6	ns
		n \overline{OE} to nBn	0.8	5.8	7.7	0.8	5.5	7.3	
V_{CCA} = 2.3V to 2.7V									
Propagation Delay ⁽²⁾	t _{PD}	nAn to nBn	0.2	3.1	4.7	0.1	2.8	4.5	ns
		nBn to nAn	0.2	3.1	4.8	0.1	3.0	4.6	
Disable Time	t _{DIS}	n \overline{OE} to nAn	1.0	3.9	7.4	1.0	5.0	7.4	ns
		n \overline{OE} to nBn	1.1	3.8	7.4	0.9	4.2	6.3	
Enable Time	t _{EN}	n \overline{OE} to nAn	0.6	3.9	5.8	0.4	3.9	5.8	ns
		n \overline{OE} to nBn	0.6	3.6	5.8	0.6	3.4	4.9	
V_{CCA} = 3.0V to 3.6V									
Propagation Delay ⁽²⁾	t _{PD}	nAn to nBn	0.1	3.0	4.5	0.1	2.7	4.1	ns
		nBn to nAn	0.1	2.9	4.5	0.1	2.8	4.2	
Disable Time	t _{DIS}	n \overline{OE} to nAn	0.7	3.7	6.7	0.7	4.4	6.7	ns
		n \overline{OE} to nBn	1.0	3.8	7.6	0.8	4.0	7.4	
Enable Time	t _{EN}	n \overline{OE} to nAn	0.6	3.2	4.7	0.4	3.3	4.7	ns
		n \overline{OE} to nBn	0.5	3.3	5.7	0.5	3.1	4.7	

NOTES:

- Specified by design and characterization, not production tested.
- t_{PD} is the same as t_{PLH} and t_{PHL}, t_{DIS} is the same as t_{PLZ} and t_{PHZ}, t_{EN} is the same as t_{PZL} and t_{PZH}.

74AVC4T245Q 4-Bit Dual-Supply Translating Transceiver with Configurable Voltage Translation and 3-State Outputs

TEST CIRCUIT



Test conditions are given in Table 1.

Definitions for test circuit:

R_L : Load resistance.

C_L : Load capacitance (includes jig and probe).

R_T : Termination resistance (equals to output impedance Z_O of the pulse generator).

V_{EXT} : External voltage used to measure switching time.

Figure 1. Test Circuit for Measuring Switching Times

Table 1. Test Conditions


SUPPLY VOLTAGE	INPUT		LOAD		V_{EXT}		
V_{CCA}, V_{CCB}	$V_I^{(1)}$	$\Delta t/\Delta V$	C_L	R_L	t_{PLH}, t_{PHL}	t_{PZH}, t_{PHZ}	$t_{PZL}, t_{PLZ}^{(2)}$
0.8V to 1.6V	V_{CCi}	$\leq 1.0\text{ns/V}$	15pF	2k Ω	Open	GND	$2 \times V_{CCo}$
1.65V to 2.7V	V_{CCi}	$\leq 1.0\text{ns/V}$	15pF	2k Ω	Open	GND	$2 \times V_{CCo}$
3.0V to 3.6V	V_{CCi}	$\leq 1.0\text{ns/V}$	15pF	2k Ω	Open	GND	$2 \times V_{CCo}$

NOTES:

- V_{CCi} is the supply voltage associated with the data input port.
- V_{CCo} is the supply voltage associated with the data output port.

74AVC4T245Q 4-Bit Dual-Supply Translating Transceiver with Configurable Voltage Translation and 3-State Outputs

WAVEFORMS




Test conditions are given in Table 1.

Measurement points are given in Table 2.

Logic levels: V_{OL} and V_{OH} are typical output voltage levels that occur with the output load.

Figure 2. Input (nAn, nBn) to Output (nBn, nAn) Propagation Delay Times



Test conditions are given in Table 1.

Measurement points are given in Table 2.

Logic levels: V_{OL} and V_{OH} are typical output voltage levels that occur with the output load.

Figure 3. Enable and Disable Times

Table 2. Measurement Points

SUPPLY VOLTAGE	INPUT ⁽¹⁾		OUTPUT		
	V_I	V_M ⁽²⁾	V_M ⁽³⁾	V_X	V_Y
0.8V to 1.6V	V_{CCI}	$0.5 \times V_{CCI}$	$0.5 \times V_{CCO}$	$V_{OL} + 0.1V$	$V_{OH} - 0.1V$
1.65V to 2.7V	V_{CCI}	$0.5 \times V_{CCI}$	$0.5 \times V_{CCO}$	$V_{OL} + 0.15V$	$V_{OH} - 0.15V$
3.0V to 3.6V	V_{CCI}	$0.5 \times V_{CCI}$	$0.5 \times V_{CCO}$	$V_{OL} + 0.3V$	$V_{OH} - 0.3V$

NOTES:

1. V_{CCI} is the supply voltage associated with the data input port.
2. The measurement points should be V_{IH} or V_{IL} when $\Delta t/\Delta V > 1.0ns/V$.
3. V_{CCO} is the supply voltage associated with the data output port.

74AVC4T245Q 4-Bit Dual-Supply Translating Transceiver with Configurable Voltage Translation and 3-State Outputs


REVISION HISTORY

NOTE: Page numbers for previous revisions may differ from page numbers in the current version.


Changes from Original (SEPTEMBER 2022) to REV.A	Page
Changed from product preview to production data.....	All

PACKAGE OUTLINE DIMENSIONS

TSSOP-16



RECOMMENDED LAND PATTERN (Unit: mm)



Symbol	Dimensions In Millimeters		
	MIN	MOD	MAX
A	-	-	1.200
A1	0.050	-	0.150
A2	0.800	-	1.050
b	0.190	-	0.300
c	0.090	-	0.200
D	4.860	-	5.100
E	4.300	-	4.500
E1	6.200	-	6.600
e	0.650 BSC		
L	0.450	-	0.750
H	0.250 TYP		
θ	0°	-	8°
ccc	0.100		

NOTES:

1. This drawing is subject to change without notice.
2. The dimensions do not include mold flashes, protrusions or gate burrs.
3. Reference JEDEC MO-153.

TAPE AND REEL INFORMATION

REEL DIMENSIONS



TAPE DIMENSIONS



NOTE: The picture is only for reference. Please make the object as the standard.

KEY PARAMETER LIST OF TAPE AND REEL

Package Type	Reel Diameter	Reel Width W1 (mm)	A0 (mm)	B0 (mm)	K0 (mm)	P0 (mm)	P1 (mm)	P2 (mm)	W (mm)	Pin1 Quadrant
TSSOP-16	13"	12.4	6.80	5.40	1.50	4.0	8.0	2.0	12.0	Q1

000001

PACKAGE INFORMATION

CARTON BOX DIMENSIONS



NOTE: The picture is only for reference. Please make the object as the standard.

KEY PARAMETER LIST OF CARTON BOX

Reel Type	Length (mm)	Width (mm)	Height (mm)	Pizza/Carton
13"	386	280	370	5

DD0002