

High Efficiency, 1MHz, 3A Synchronous Step Down Regulator


General Description

The SY8883 is a high efficiency 1MHz synchronous step down DC/DC regulator, which is capable of delivering up to 3A output current. It can operate over a wide input voltage range from 2.5V to 5.5V and integrate main switch and synchronous switch with very low $R_{DS(ON)}$ to minimize the conduction loss.

The SY8883 integrates reliable latch off function when output over voltage, output short or thermal shutdown happens.

The low output voltage ripple, the small external inductor and the capacitor sizes are achieved with 1MHz switching frequency.

Ordering Information



Ordering Number	Package type	Note
SY8883DFC	DFN2×2-8	--

Features

- 2.5V to 5.5V Input Voltage Range
- 55μA Low Quiescent Current
- Low $R_{DS(ON)}$ for Internal Switches (Top/Bottom): 85mΩ /60mΩ
- High Switching Frequency 1MHz Minimizes the External Components
- Internal Soft-start Limits the Inrush Current
- 100% Dropout Operation
- Power Good Indicator
- Reliable Latch off Function When:
 - Output Under Voltage
 - Thermal Shutdown
 - Output Voltage>120% of Regulated Voltage
- Output Auto Discharge Function
- RoHS Compliant and Halogen Free
- Compact Package: DFN2×2-8

Applications

- Set Top Box
- USB Dongle
- Media Player
- Smart Phone

Typical Application




Figure1. Typical Application Circuit

Inductor and C_{OUT} Selection Table

V_{OUT} [V]	L [μH]	C_{OUT} [μF]			
		10	22	32	44
1.2	1.0		✓	☆	✓
	1.5		✓	✓	✓
1.8/3.3	1.0		☆	✓	✓
	1.5		✓	✓	✓

Note: '☆' means recommended for most applications.





Figure2. Efficiency vs. Output Current

Pin out (Top View)



Top Mark: CWFxyz (device code: CWF, x=year code, y=week code, z= lot number code)

Pin Name	Pin No.	Pin Description
FB	1	Output feedback pin. Connect this pin to the center point of the output resistor divider (as shown in Figure 1) to program the output voltage: $V_{OUT}=0.6 \times (1+R_H/R_L)$.
PG	2	Power good indicator. Power good indicator (open drain output). Low if the output < 90% or the output >120% of regulation voltage; High otherwise. Connect a pull-up resistor to the input.
IN	3	Input pin. Decouple this pin to GND pin with at least a 10 μ F ceramic capacitor.
PGND	4/Exposed Paddle	Power ground pin.
NC	5	No connection.
LX	6	Inductor pin. Connect this pin to the switching node of inductor.
EN	7	Enable control. Pull high to turn on. Do not float.
SGND	8	Analog ground pin.

Block Diagram




Figure3. Block Diagram

Absolute Maximum Ratings (Note 1)

Supply Input Voltage	-0.3V to 6.0V
FB, EN, PG Voltage	-0.3V to $V_{IN} + 0.6V$
LX Voltage	-0.3V ^{(*)1} to 6.0V ^{(*)2}
Power Dissipation, P_D @ $T_A = 25\text{ }^{\circ}C$	1.4W
Package Thermal Resistance (Note 2)	
θ_{JA}	70 $^{\circ}C/W$
θ_{JC}	25 $^{\circ}C/W$
Junction Temperature Range	-40 $^{\circ}C$ to 150 $^{\circ}C$
Lead Temperature (Soldering, 10 sec.)	260 $^{\circ}C$
Storage Temperature Range	-65 $^{\circ}C$ to 150 $^{\circ}C$
^{(*)1} LX Voltage Tested Down to -3V <20ns	
^{(*)2} LX Voltage Tested Up to +7V <20ns	

Recommended Operating Conditions (Note 3)

Supply Input Voltage	2.5V to 5.5V
Junction Temperature Range	-40 $^{\circ}C$ to 125 $^{\circ}C$
Ambient Temperature Range	-40 $^{\circ}C$ to 85 $^{\circ}C$

Electrical Characteristics

($V_{IN} = 5V$, $V_{OUT} = 1.8V$, $L = 1.0\mu H$, $C_{OUT} = 22\mu F$, $T_A = 25^\circ C$, unless otherwise specified)


Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Input Voltage Range	V_{IN}		2.5		5.5	V
Input UVLO Threshold	V_{UVLO}			2.45	2.5	V
Input UVLO Hysteresis	V_{YST}			150		mV
Quiescent Current	I_Q	$V_{FB}=105\% \times V_{REF}$		55		μA
Shutdown Current	I_{SHDN}	$V_{EN}=0V$		0.1	1	μA
Feedback Reference Voltage	V_{REF}	$I_{OUT}=0.5A$, CCM	0.591	0.6	0.609	V
LX Node Discharge Resistance	R_{DIS}			50		Ω
Top FET R_{ON}	$R_{DS(ON)1}$			85		m Ω
Bottom FET R_{ON}	$R_{DS(ON)2}$			60		m Ω
EN Input Voltage High	$V_{EN,H}$		1.2			V
EN Input Voltage Low	$V_{EN,L}$				0.4	V
PG Threshold for Under Voltage Detection	$V_{PG, UVP}$			90		%
PG Low Delay Time for Under Voltage Detection	$t_{UVP,DLY}$			10		μs
PG Threshold for Over Voltage Detection	$V_{PG, OVP}$			120		%
PG Low Delay Time for Over Voltage Detection	$t_{OVP,DLY}$			20		μs
Min ON Time	$t_{ON, MIN}$			50		ns
Maximum Duty Cycle	D_{MAX}		100			%
Turn on Delay Time	$t_{ON, DLY}$	from EN high to LX start switching		0.5		ms
Soft-start Time	t_{SS}	V_{OUT} from 0% to 100%		1		ms
Switching Frequency	f_{SW}	$I_{OUT}=0.5A$, CCM		1.0		MHz
Top FET Current Limit	$I_{LMT, TOP}$		3.7			A
Output Under Voltage Protection Threshold	V_{UVP}			50		% V_{REF}
Output UVP Delay	$t_{UVP, DLY}$			5		μs
Thermal Shutdown Temperature	T_{SD}			160		$^\circ C$

Note 1: Stresses beyond the “Absolute Maximum Ratings” may cause permanent damage to the device. These are stress ratings only. Functional operation of the device at these or any other conditions beyond those indicated in the operational sections of the specification is not implied. Exposure to absolute maximum rating conditions for extended periods may affect device reliability.


Note 2: θ_{JA} of SY8883DFC is measured in the natural convection at $T_A = 25^\circ C$ on a 2-oz two-layer Silergy evaluation board. Paddle of DFN2 $\times$ 2-8 package is the case position for θ_{JC} measurement.

Note 3: The device is not guaranteed to function outside its operating conditions.

DFN2×2-8 Package Outline Drawing



Top View




Bottom View




Detail A

Pin1 Identifier(Two options)



Side View




Recommended PCB Layout (Reference)


Notes: All dimensions are in millimeters and don't include mold flash & metal burr.

Taping & Reel Specification

1. DFN2×2



2. Carrier Tape & Reel specification for packages



Package types	Tape width (mm)	Pocket pitch(mm)	Reel size (Inch)	Trailer length(mm)	Leader length (mm)	Qty per reel
DFN2×2	8	4	7"	400	160	3000

3. Others: NA